

A quick summary

The Yale 8 range of advanced multipoint locks covers door leaf height ranges from 1700mm* to 2210mm* and is available in two lock options:

Yale 8 5-point lock and latch system

Yale 8+ 5-point lock and latch system with additional top and bottom shootbolts

The range offers exceptional strength and versatility, accommodating a complete range of door leaf height specifications, with or without shootbolts.



The Yale 8 lock system is manufactured in the UK and has been rigorously tested to meet the performance and security requirements of PAS 23 and PAS 24.

* Yale 8+ Minimum size: Without shoot bolts, lock centre of 925mm. Maximum size with shoot bolts, lock centre at 1045mm.

Yale 8

- High-security tandem bolt system
- Stainless main steel components for corrosion resistance
- Unique 'Operation Assist' anti-friction pad system
- Advanced 'Compression Adjust' system
- Counter-opposing security bolts for anti-lift facility
- Clean face lock - no protruding rollers
- Stainless steel, non-handed flush-line one-piece keep set
- Wide range of door heights
- Lock-tested to PAS 23 (performance) and PAS 24 (security)
- Meets Police-approved Secured by Design specification
- Manufactured in the UK to ISO 9001: 2008
- 10-year mechanical guarantee*
- Optional top and bottom shootbolts - ideal for tall doors & double doors*

*Yale 8+ only
*Subject to terms and conditions

Peace of mind



FM09180
BS EN ISO 9001



EMS86980
BS EN ISO 14001



OHS523157
BS OHSAS 18001



BBA
APPROVED
PRODUCT
CONSTRUCTION
SECURITY



Secured by Design
Official Police Security Initiative



KM12895
BS EN 12808
PROFILE



KM33523
BS7950/BS EN 12608
ENHANCED SECURITY
WINDOWS



KM56791
PAS23-1 & PAS24-1
SYSTEM SUPPLIER
GENERAL & ENHANCED
SECURITY DOORS



CPD
MEMBER
Construction CPD
Certification
Service



PVC
aware.org



The **NEW**
advanced
multipoint
locking system
for **PVC-U** doors



Stafford Park 6, Telford TF3 3AT
T: +44(0)1952 290910 F: +44(0)1952 290460
mail@safeware-security.co.uk www.safeware-security.co.uk



High-security tandem bolt system

- Unique, hook and linear bolt combination locking points
- Linear compression bolt motion for smooth operation
- Easier to install and less prone to damage than traditional rollers
- Assists door compression with maximum security
- Allows greater door leaf-to-frame cover with maximum clearance
- 25mm counter-opposing hook-bolts for anti-lift
- Flush lock face - no protruding rollers
- Secure and robust



Centre hookbolt

- Extra security at door centre
- Provides higher resistance to attack
- 25mm throw hooks maintain anti-separation security at all times



Quick-change reversible latch

- Easily reversible for rapid re-handing
- Dual unsprung followers (split spindle) for interchangeable front & back door applications in one lock
- Handle-driven snib facility - simple latch retaining system to prevent accidental lock-out



Optional shootbolt*

- Optional top and bottom shootbolts to ensure secure and positive leaf engagement at heads and cills
- Ideal for double doors
- Caters for all door heights from short to tall



A superior locking solution

The Yale 8 range of advanced multipoint locks has been designed exclusively for Profile 22 to achieve a superior locking solution for PVC-U hinged doors.

Utilising unique anti-friction technology and linear compression bolt-motion, the Yale 8 range offers smooth and easy operation, providing effortless lock engagement and a greater degree of security than conventional roller and bolt door locks.

Utilising all stainless steel main components, the Yale 8 range provides excellent durability and corrosion resistance.



Flush-line one-piece keep set

- Dedicated one-piece keep set for added strength and security
- Die-cast base construction ensures positive and secure fit every time
- Flush-line covers that can be easily removed during door frame installation for concealed fixing
- Stainless steel components for exceptional durability and corrosion resistance
- Non-handed for minimal stock-holding



'Compression Adjust' technology

- Advanced 'Compression Adjust'* system for simpler and more effective compression adjustment
- Compression range +/- 2mm from nominal
- Easily accessible to aid fitting



'Operation Assist' anti-friction pads

- Unique 'Operation Assist' anti-friction pad system for significantly reduced operating force
- Smooth and effortless lock engagement



Single or double shootbolt keep with 'Compression Adjust' system

- Advanced 'Compression Adjust'* technology - for single, French or double doors
- Compression range +/- 2mm from nominal
- Die cast base construction ensures positive and secure fit every time
- Simple and precise



*Patent applied for